

Compliance Document

No. D 086470 0189 Rev. 00

Holder of Certificate: **Ginlong Technologies Co., Ltd.**
No.57 Jintong Road
Binhai Industrial Park, Xiangshan
315712 Ningbo, Zhejiang
PEOPLE'S REPUBLIC OF CHINA

Product: **Converter**
Hybrid Inverter

This Compliance document confirms the compliance with the listed standards on a voluntary basis. It refers only to the sample submitted for testing and certification and does not certify the quality or safety of the serial products. For details see: www.tuvsud.com/ps-cert

Test report no.: 704092304894-00

Date, 2024-04-23



(Zhengdong Ma)

Compliance Document

No. D 086470 0189 Rev. 00

Model(s): S6-EH3P29.9K-H, S6-EH3P30K-H, S6-EH3P40K-H,
S6-EH3P50K-H

Parameters:

Model	S6-EH3P29.9K-H	S6-EH3P30K-H
1) PV input		
Max. input voltage	DC 1000 V	DC 1000 V
MPPT voltage range	DC 150 - 850 V	DC 150 - 850 V
Max. input current	3x40A	3x40A
Isc PV (absolute maximum)	3x60A	3x60A
2) Battery input		
Battery type	Li-ion	Li-ion
Battery voltage range	DC 150 - 800 V	DC 150 - 800 V
Max. charge current:	DC 2x70 A	DC 2x70 A
Max. discharge current:	DC 2x70 A	DC 2x70 A
3) AC-output (Grid side)		
Rated output voltage:	3/N/PE AC 230/400 V	3/N/PE AC 230/400 V
Rated output frequency:	50 Hz	50 Hz
Max. (Rated) output current:	43.2A	43.3A
Max. (Rated) apparent output power	29900VA	30000VA
Power factor range	-0.8, ...,1, ..., +0.8	-0.8, ...,1, ..., +0.8

Compliance Document

No. D 086470 0189 Rev. 00

Model	S6-EH3P40K-H	S6-EH3P50K-H
1) PV input		
Max. input voltage	DC 1000 V	DC 1000 V
MPPT voltage range	DC 150 - 850 V	DC 150 - 850 V
Max. input current	4x40A	4x40A
Isc PV (absolute maximum)	4x60A	4x60A
2) Battery input		
Battery type	Li-ion	Li-ion
Battery voltage range	DC 150 - 800 V	DC 150 - 800 V
Max. charge current:	DC 2x70 A	DC 2x70 A
Max. discharge current:	DC 2x70 A	DC 2x70 A
3) AC-output (Grid side)		
Rated output voltage:	3/N/PE AC 230/400 V	3/N/PE AC 230/400 V
Rated output frequency:	50 Hz	50 Hz
Max. (Rated) output current:	57.7A	72.2A
Max. (Rated) apparent output power	40000VA	50000VA
Power factor range	-0.8, ..., 1, ..., +0.8	-0.8, ..., 1, ..., +0.8

**Tested
according to:**

NRS 097-2-1:2017 Edition 2.1