

Solis Solarator Series

Experience Uninterrupted Power with Solis Energy Storage Inverters

Energy Storage Inverters

S6-EH3P(80-125)K10-NV-YD-H

Three Phase | High Voltage



Smart Energy Management

- AI intelligently manages charging and discharging based on TOU (Time-of-Use) tariffs
- Adapt to third party VPP platform, frequency service provider



High Performance

- Supports 100% three-phase unbalanced output
- 200% PV input capacity to maximize solar energy utilization
- Max. 200% overload capability in off-grid mode
- Charging and discharging currents of up to 200A
- Switching time < 10ms



Flexible & Scalable

- Compatible with mainstream lithium batteries
- Support Solis C&I battery solution
- Easily expand system capacity using parallel connections and AC coupling



Simple & Fast Configuration

- 7-inch LCD screen for an intuitive user experience
- Bluetooth app support for quick and easy setup

SOUTH AFRICA

t: +27 010 222 0181

w: solisinverters.com/za

e: sales@ginlong.com

saservice@solisinverters.com



DATASHEET

S6-EH3P(80-125)K10-NV-YD-H

Models	80K	100K	125K
Input DC (PV side)			
Recommended max. PV array size	160 kW	200 kW	240 kW
Max. usable PV input power	160 kW	200 kW	240 kW
Max. input voltage		1000 V	
Rated voltage		600 V	
Start-up voltage		180 V	
MPPT voltage range		150 - 950 V	
Max. input current		10 × 42 A	
Max. short circuit current		10 × 60 A	
MPPT number / Max. input strings number		10 / 20	
Battery			
Battery type		Li-ion	
Battery voltage range		300 - 950 V	
Max.charge / discharge current		200 A / 100 A + 100 A	
Number of battery ports		2	
Max. charge / discharge current of each port		100 A	
Communication		CAN / RS485	
Output AC (Grid side)			
Rated output power	80 kW	100 kW	125 kW
Max. apparent output power	80 kVA	100 kVA	125 kVA
Rated grid voltage		3/N/PE, 220 V / 380 V, 230 V / 400 V	
Rated grid frequency		50 Hz	
Rated grid output current	121.6 A / 115.5 A	152 A / 144.3 A	180.4 A / 189.9 A
Power factor		> 0.99 (0.8 leading - 0.8 lagging)	
THDi		< 3%	
Input AC (Grid side)			
Max. input current		250 A	
Output AC (Back-up)			
Rated output power	80 kW	100 kW	125 kW
Max. apparent output power	1.2 times of rated power, 10 mins; 1.4 times of rated power, 100 s; 1.6 times of rated power, 10 s; 2 times of rated power, 200 ms		1.2 times of rated power, 100 s 1.4 times of rated power, 10 s 1.6 times of rated power, 200 ms
Back-up switch time		< 10 ms	
Rated output voltage		3/N/PE, 220 V / 380 V, 230 V / 400 V	
Rated frequency		50 Hz	
THDv (@linear load)		< 2%	
Efficiency			
Max. efficiency		97.6%	
EU efficiency		97.2%	
BAT charged / discharged to AC max. efficiency		97.0%	
Protection			
Anti-islanding protection		Yes	
Output over current protection		Yes	
Short circuit protection		Yes	
Integrated DC switch		Yes	
DC reverse-polarity protection		Yes	
Surge protection		DC Type II / AC Type II	
Integrated AFCI 2.0		Optional	
Protection class / Over voltage category		I / II	
General Data			
Max. allowable phase imbalance (grid & back-up)		100%	
Max. power per phase (grid & back-up)	26.66 kW	33.33 kW	41.66 kW
Dimensions (W × H × D)		1174 × 814 × 400 mm	
Weight		170 kg	
Topology		Transformerless	
Operating ambient temperature range		-25 ~ +60°C	
Ingress protection		IP66	
Cooling concept		Intelligent fan-cooling	
Max. operation altitude		3000 m	
Grid connection standard	G99, VDE-AR-N 4105/VDE V 0124, EN 50549-1&2/EN 50549-10, VDE 0126/UTE C 15/VFR:2019, NTS 631/ RD 1699/RD 244/UNE 206006/UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, MEA, PEA,PORTARIA Nº 140, DE 21 DE MARÇO DE 2022		
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4, EN 55011		
Features			
PV connection	MC4 Quick connection plug		
Battery connection	Terminal connector		
AC connection	Terminal block		
Display	7.0" LCD display & Bluetooth + APP		
Communication	CAN, RS485-115200, Ethernet, Optional: Wi-Fi, Cellular, LAN		